

Aluminum Counter Door Specifications

1. General

1.1.Summary

A. Counter doors excluding design, construction and preparation of openings; finish or field painting; access panels; electrical wiring, conduit, wire, fuses and disconnect switches

2. Products

2.1.Materials

- A. Manufacturer: R&S Manufacturing Model S____
- B. Mounting: Face of wall or between-jamb
- C. **Operation:** Push-up is standard. Chain hoist, or motor operation are optional.
- D. **Curtain:** Interlocking type 15 slats are extruded from 6063 alloy aluminum. Endlocks are riveted to slats to maintain curtain alignment. Bottom of curtain is reinforced by an extruded aluminum tubular footpiece.
- E. **Guides:** Extruded aluminum guides are bolted to aluminum wall angles. Guides are fitted with nylon pile wearstrips.
- F. **Brackets:** Steel plate brackets are bolted to wall angles to support curtain and barrel, and provide mounting for hood.
- **G. Barrel:** Steel pipe houses torsion spring assembly and supports curtain with a maximum deflection of .03 inch per foot of width. Torsion springs are mounted on a continuous cold rolled steel shaft, adjustable by a torsion wheel outside one bracket.
- H. **Hood:** Formed from aluminum sheet, reinforced with top and bottom flanges to limit deflection.
- I. Locking: Slidebolt locks standard, cylinder locks optional.

2.2.Finish

A. Aluminum slats, footpiece, guides, and hood are clear anodized. Steel brackets receive one coat of rust inhibiting primer.

3. Execution

3.1.Installation

A. Counter doors are to be installed by an R&S authorized representative in accordance with R&S installation instructions.



Aluminum Counter Door Options

Cylinder Locks: Lock cylinder mounted in tubular aluminum footpiece activate lock bolts into each guide

Inside Tension: Tension wheel that is on the inside of the bracket and covered by the hood

Tubular Motor Operator: Completely contained within the barrel for counter doors in limited usage

applications

Finish: Standard clear anodized finish may be upgraded to dark bronze